

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: C09K 5/04	A1	(11) International Publication Number: WO 95/08602 (43) International Publication Date: 30 March 1995 (30.03.95)
(21) International Application Number: PCT/GB94/02042 (22) International Filing Date: 20 September 1994 (20.09.94) (30) Priority Data: 9319540.2 22 September 1993 (22.09.93) GB (71) Applicant (for all designated States except US): STAR REFRIGERATION LIMITED [GB/GB]; Thornliebank Industrial Estate, Glasgow G46 8JW (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): PEARSON, Stephen, Forbes [GB/GB]; 9/2 Whistlefield Court, Bearsden, Glasgow G61 1PZ (GB). (74) Agents: McCALLUM, William, Potter et al.; Cruickshank & Fairweather, 19 Royal Exchange Square, Glasgow G1 3AE (GB).		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ). Published <i>With international search report.</i>
(54) Title: REPLACEMENT REFRIGERANT COMPOSITION (57) Abstract A refrigerant composition for use in a vapour-compression refrigeration apparatus as a replacement for currently used refrigerants R22 and R12 comprises a mixture of pentafluoroethane (R125), tetrafluoroethane (R134a), a hydrocarbon selected from isobutane (R600a) and propane (R290), and optionally octafluoroethane (R218). The composition contains no chlorine atoms and is non-depleting to atmospheric ozone; but specific compositions have pressure-temperature relations substantially the same as R22 and R12 thereby allowing their use as direct replacements therefor in existing refrigeration apparatus.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

- 1 -

REPLACEMENT REFRIGERANT COMPOSITIONTECHNICAL FIELD

The present invention relates to a refrigerant composition, which contains no chlorine atoms.

BACKGROUND

Chlorofluorocarbon (CFC) gases, such as refrigerant R12 (CCl_2F_2), have been used for many years as refrigerants and are especially used in domestic refrigerators and car air conditioning systems. However, such gases have been implicated in environmental damage. These gases, which are very inert, are released from refrigeration systems at ground level and diffuse into the upper atmosphere. Because of their inertness, the gases are able to survive without decomposition until they reach the stratosphere where they are broken down by ultra-violet radiation, releasing chlorine atoms which catalyse breakdown of the stratospheric ozone layer. There has recently been considerable concern about reduction in stratospheric ozone levels and this has led to proposed restrictions and prohibitions on certain CFC's.

Other refrigerants such as chlorodifluoromethane (R22) are environmentally less objectionable as they tend to be degraded naturally at lower levels of the atmosphere before reaching the ozone layer. However, R22 contains

- 2 -

chlorine and is still considered to contribute to ozone depletion. Further, R22 has a higher index of compression than, for example, R12, such that compressor discharge temperatures become excessive at pressure ratios which would not cause excessive discharge temperatures if R12 were being used.

It is among the objects of the present invention to provide a refrigerant composition which does not contain any chlorine but which has acceptable refrigerant characteristics for use in vapour compression refrigerators as a replacement for refrigerant R22 and/or R12 in existing refrigeration equipment.

SUMMARY OF THE INVENTION

According to a first aspect of the present invention there is provided a refrigerant composition for use in a refrigeration apparatus which comprises a mixture of:

- (i) pentafluoroethane;
- (ii) tetrafluoroethane; and
- (iii) a hydrocarbon selected from isobutane, propane and mixtures thereof.

The composition may optionally also contain (iv) octafluoropropane.

A further aspect of the present invention provides a method of refrigeration which employs the composition as a refrigerant medium, particularly a vapour-compression refrigerator.

- 3 -

A still further aspect provides a refrigeration apparatus which employs the composition as a refrigerant medium, particularly a vapour-compression refrigerator.

None of the components of the mixture contribute to ozone depletion nor are any toxic to humans. Further, the mixture may be used with a variety of existing lubricants as conventionally used in vapour compression refrigeration apparatus, including mineral oil lubricants, alkylbenzene lubricants and polyolester lubricants. Specialised lubricants are not required.

It is found that by forming mixtures of these three or four components in chosen proportions, it is possible to provide refrigerant compositions which have pressure-temperature relationships which are sufficiently similar to those of the current refrigerants R22 and R12 to allow their use as replacements therefor in existing refrigeration equipment. The pressure-temperature relationship refers to the vapour pressure of the refrigerant composition at various temperatures corresponding to those used in the refrigeration apparatus. Thus, the design pressure capabilities of the apparatus are not exceeded. It is also found that the refrigeration capacities of the compositions of the invention may be arranged to be similar to those of the current refrigerants R22 and R12, so that the refrigeration capacity (i.e. the amount of cooling produced) of refrigeration apparatus intended to be used

- 4 -

with R22 or R12 respectively is substantially unaffected.

Advantageously, the compositions of the invention tend to have lower compressor discharge temperatures than the corresponding conventional refrigerant.

The pentafluoroethane (R125) is preferably present in an amount of 0.5 to 60 wt%, particularly 1 to 50 wt %. In compositions for use as an R22 replacement, R125 is preferably present in percentages at the upper end of this range e.g. 20 to 45 wt %, particularly 27 to 40 wt %. In compositions for use as an R12 replacement, the amount of R125 is usually at the low end of this range e.g. 0.5 to 10 wt%, especially 1 to 10 wt.%.

The tetrafluoroethane (preferably R134a) is generally present in an amount of 30 to 98 wt%, particularly 30 to 90 wt.%, and usually forms the major proportion of the composition. When used as an R22 replacement, the composition of the invention usually employs 45 to 70% of R134a; whereas for use in replacing R12 the percentage of R134a usually lies in the range 80 to 90 wt.%.

For safety reasons, the hydrocarbon should preferably be present in a non-flammable proportion so that in the event of a leak of refrigerant medium into the atmosphere, no explosive or flammable mixture is produced. A hydrocarbon content of 1 to 11 wt%, particularly 2 to 10 wt.%, and preferably 3 to 5 wt.% is preferred. In particular, a non-flammable composition is one which contains the components of the mixture in such a ratio

- 5 -

that when the composition is mixed with air in practical proportions (e.g. in the event of a leak) no flammable mixture results. The fluorocarbon components R125 and R218 possess fire-retardant properties to a degree. Thus, the assessment of flammability characteristics is not necessarily predictable but can be determined by routine experimentation (see, for example, our patent US 5108637).

The octafluoropropane (R218) is an optional constituent and is typically present in an amount of 0 to 20 wt.%. It has a long lifetime when released into the atmosphere so that future legislation may make its use less preferred. It is generally present in an amount of 4 to 15 wt%, particularly 5 to 10 wt.%.

In a preferred embodiment as an R22 replacement, the composition comprises a mixture of:

- (i) 20 to 45 wt% pentafluoroethane (R125);
- (ii) 45 to 70 wt% tetrafluoroethane (e.g. R134a);
- (iii) 2 to 8 wt% isobutane (R600a); and
- (iv) 5 to 10 wt% octafluoroethane (R218).

The pressure-temperature relationship of this mixture is similar to that of chlorodifluoroethane (R22). The refrigerating performance is also similar within acceptable limits. However, the mixture has a lower index of compression than R22, resulting in lower compressor discharge temperatures, and of course contains no chlorine.

A preferred embodiment for use as an R12 replacement comprises a mixture of:

- 6 -

- (i) 0.5 to 5 wt% pentafluoroethane (R125);
- (ii) 75 to 98 wt% tetrafluoroethane (R134a);
- (iii) 1 to 6 wt% isobutane (R600a); and
- (iv) 6 to 15 wt% octafluoroethane (R218).

DESCRIPTION OF PREFERRED EMBODIMENTS

These and other aspects of the present invention will now be described, by way of example in conjunction with the drawings; wherein.

Figure 1 shows the pressure-temperature diagrams for a composition according to the invention (RX3) and conventional R22 refrigerant; and

Figure 2 shows the pressure-temperature diagrams for a further composition according to the invention (RX2) and conventional R12 refrigerant.

The composition according to the invention (RX3) comprised 40 wt.% R125, 6 wt.% R218, 50 wt.% R134a and 4 wt.% R600a and is intended as a replacement for currently used R12 refrigerant.

The composition in liquid form was introduced into an evacuated vessel and allowed to equilibrate. The vessel was heated to various temperatures and the vapour pressure in the presence of liquid noted. It can be seen from Figure 1 that the pressure-temperature relationship is very similar to that for R22, which means that the pressures encountered using the composition of the invention will not in substance exceed those of R22. Thus

- 7 -

the design pressures of the apparatus will not be exceeded.

Figure 2 shows the pressure-temperature relationship for a further composition (RX2) according to the invention in comparison to conventional R12 refrigerant. This was obtained following the procedure described in relation to Figure 1.

The composition (RX2) according to the invention comprised 1 wt% R125, 9 wt% R218, 87 wt% R134a and 3 wt% R600a.

It will be noted that the pressure-temperature relationship for RX2 is very similar to R12, so that it is suitable as a chlorine-free replacement therefor without requiring substantial changes to the refrigeration apparatus.

EXAMPLE

A water chilling system in everyday use and employing refrigerant R12 developed a leak at the hermetically sealed motor terminals. The leak was repaired and the compressor replaced. The system was evacuated and recharged with refrigerant composition RX2 according to the invention of composition given above. Table 1 shows performance characteristics before and after charging with RX2.

The performance using RX2 according to the invention is similar or slightly better than the performance using conventional refrigerant R12.

- 8 -

In Table 1 the abbreviations have the following meanings.

SUCT PRESS and DISCH PRESS are the compressor suction and discharge pressures, respectively.

SUCT TEMP COMP and DISCH TEMP EVAP COIL are compressor suction and discharge temperatures, respectively.

SUCT TEMP EVAP COIL is the suction temperature at the evaporator coil.

LIQ TEMP BEFORE and AFTER HEAT EXCH are the respective temperatures before and after the heat exchanger.

TABLE 1

(WATER CHILLER - REFRIGERANT RX2 as replacement for R12)

R12	SUCT PRESS psig	DISCH PRESS psig	SUCT TEMP COMP oC	DISCH TEMP COMP oC	SUCT TEMP EVAP oC	COIL	LIQ TEMP BEFORE HEAT EXCH. oC	LIQ TEMP AFTER HEAT EXCH. oC	WATER TANK TEMP oC
1	30	140	16	57.7	12.7		30.5	11.5	13.2
2	28	130	15.8	62.4	8.5		28.5	11.0	9
3	22	130	13	65	4.9		28	12.4	4.5
<u>RX2 NEW COMPRESSOR AND REFRIGERANT CHARGE</u>									
1	20	140	14	69	4		38	33	3.5
2	20	150	14	74	6		38	36	3
3	20	145	13	70	4.5		37	36	2.5
4	20	143	13	69	4.6		37	35.5	2.7
5	30	155	16	70	10.1		35	28	8
6	20	143	13	69	4		36	30	3

CLAIMS

1. A refrigerant composition for use in a refrigeration apparatus which comprises a mixture of:

- (i) pentafluoroethane;
- (ii) tetrafluoroethane; and
- (iii) a hydrocarbon selected from isobutane, propane and mixtures thereof.

2. A composition according to any preceding claim wherein the pentafluoroethane is present in an amount of 0.5 to 60 wt%.

3. A composition according to claim 2 wherein the pentafluoroethane is present in an amount of 1 to 50 wt%.

4. A composition according to any preceding claim wherein the tetrafluoroethane is present in an amount of 30 to 98 wt%.

5. A composition according to claim 4 wherein the tetrafluoroethane is present in an amount of 30 to 90 wt%.


6. A composition according to any preceding claim wherein the hydrocarbon is present in an amount of 1 to 11 wt%, and the composition is non-flammable.


- 11 -

7. A composition according to claim 6 wherein the hydrocarbon is present in an amount of 2 to 10 wt%.
8. A composition according to any preceding claim wherein the hydrocarbon is isobutane.
9. A composition according to any preceding claim which further comprises:
 - (iv) octafluoropropane.
10. A composition according to claim 9 which comprises up to 20 wt% of octafluoropropane.
11. A composition according to claim 10 wherein the octafluoropropane is present in an amount of 5 to 10 wt%.
12. A refrigerant composition for use as a replacement for refrigerant R22 in a refrigeration apparatus which comprises a mixture of:
 - (i) 20 to 45 wt% pentafluoroethane;
 - (ii) 45 to 70 wt% tetrafluoroethane;
 - (iii) 2 to 8 wt% isobutane; and
 - (iv) 5 to 10 wt% octafluoroethane.
13. A refrigerant composition for use as a replacement for refrigerant R12 in a refrigeration apparatus which comprises a mixture of:

- 12 -

- (i) 0.5 to 5 wt% pentafluoroethane;
- (ii) 75 to 98 wt% tetrafluoroethane;
- (iii) 1 to 6 wt% isobutane; and
- (iv) 6 to 15 wt% octafluoroethane.

1 / 2FIG.1

2/2FIG. 2

INTERNATIONAL SEARCH REPORT

 Intern. Appl. Application No
 PCT/GB 94/02042

 A. CLASSIFICATION F SUBJECT MATTER
 IPC 6 C09K5/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

 Minimum documentation searched (classification system followed by classification symbols)
 IPC 6 C09K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 017, no. 478 (C-1104) 31 August 1993 & JP,A,05 117 643 (MATSUSHITA ELECTRIC IND CO LTD) 14 May 1993 see abstract ---	1-7
X	PATENT ABSTRACTS OF JAPAN vol. 016, no. 176 (C-0934) 27 April 1992 & JP,A,04 018 485 (SANYO ELECTRIC CO LTD) 22 January 1992 see abstract ---	1-8
X	WO,A,93 15163 (ALLIED SIGNAL) 5 August 1993 see the whole document --- -/--	1-7

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

6 December 1994

Date of mailing of the international search report

15.12.94

Name and mailing address of the ISA

 European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

NICOLAS, H

INTERNATIONAL SEARCH REPORT

Inter. Appl. No.
PCT/GB 94/02042

C(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO,A,92 11338 (DU PONT DE NEMOURS) 9 July 1992 see abstract; claims 1,2,10,11 ---	1-13
A	EP,A,0 539 952 (MATSUSHITA) 5 May 1993 see abstract; claims 1-6 -----	1-13

INTERNATIONAL SEARCH REPORT

information on patent family members

Intern. Appl. Application No

PCT/GB 94/02042

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-9315163	05-08-93	AU-B- 3602193 CN-A- 1076713	01-09-93 29-09-93
WO-A-9211338	09-07-92	AU-A- 9143391 AU-A- 9173891 BR-A- 9107225 BR-A- 9107226 CN-A- 1063300 CN-A- 1063301 EP-A- 0563220 EP-A- 0563305 JP-T- 6503828 JP-T- 6503832 WO-A- 9211339 US-A- 5185094	22-07-92 22-07-92 05-04-94 05-04-94 05-08-92 05-08-92 06-10-93 06-10-93 28-04-94 28-04-94 09-07-92 09-02-93
EP-A-0539952	05-05-93	JP-A- 5117643	14-05-93